

SPECIFICATION OF PRODUCT

Rechargeable Li-ion Polymer Battery
Model : SPB655060(2250mAh)

SAEHAN-ENERTECH. INC.

710-3, Yongtan-Dong, Chung-Ju , Chung-buk , Korea

TEL: 82-43-850-1951 FAX: 82-43-850-1999

www.saeahan-enertech.com

Issued	Checked	Approved

1. Nominal Specifications

	Item		Specification
1	Battery Type		Rechargeable Li-ion Polymer Battery
2	Model		SPB655060
3	Nominal Capacity		2250mAh (0.2C discharge)
4	Nominal Voltage		3.7V
5	Energy Density	Volume	426 Wh/L
		Weight	200 Wh/kg
6	Charging Mode		CC-CV (constant voltage with limited current)
7	Charging Current		Standard : 1125mA (0.5C) Rapid : 2250mA (1.0C)
8	Charging Voltage		4.2V
9	Max. Charge Current		2250 mA
10	Max. Discharge Current		4500 mA (2.0C)
11	Cell Dimension (mm)		Thickness : 6.5±0.1 mm (fully charged cell) Width : Max 50.0 mm Height : 60 +1.5/-0.0 mm
12	Cell Weight		less than 41.5 g
13	AC Impedance (at 1kHz)		20mΩ or less
14	Operating Temperature		Charge : 0 to 45℃ Discharge: -20 to 60℃
15	Storage Temperature		-10 ~ 40℃ (Within 6 months)
16	Overcharge Test		NE, NF (1A, 5V)
17	External Short-circuit Test		NE, NF (4.2V, 100mΩ)
18	Heating Test		NE, NF (130℃, 60min)
19	Crush		NE, NF (13kN force)

2. Out View drawing for SPB655060

